

QUANTUM

		5700 P	5700 S	4700 P	4700 S	3800 P	3500 P
Load volume	m ³	37	34.5	32	29	33.2	28
Load volume with medium compression	m ³	66.6	58.7	57.6	49.3	59.8	50.4
Hitching							
Top hitching with hitching ring		●	●	●	●	●	●
Bottom hitching with Scharmüller K80 ball coupling		○	○	○	○	○	○
Bottom hitching with hitching ring ¹		○	○	○	○	○	○
Pick-up							
Clearing width	mm	1800	1800	1800	1800	1800	1800
Diameter	mm	320	320	320	320	320	320
No. of tine rows	Qty	5	5	5	5	5	5
Guide wheel tyres		16 x 6.50-8	16 x 6.50-8	16 x 6.50-8	16 x 6.50-8	16 x 6.50-8	16 x 6.50-8
Ground clearance with articulating drawbar raised	mm	680	680	680	680	680	680
Rotor/knives							
Width	mm	1586	1586	1586	1586	1586	1586
Diameter	mm	860	860	860	860	860	860
No. of tine rows	Qty	9	9	9	9	9	9
Knives	Qty	33	33	33	33	33	33
Shortest theoretical chop length	mm	45	45	45	45	45	45
Scraper floor							
Chains	Qty	2 x 2	2 x 2	2 x 2	2 x 2	2 x 2	2 x 2
Two-speed scraper floor drive		●	●	○	○	–	–
Dimensions/weights							
Overall length	mm	9410	9800	8310	8700	9250	8100
Overall width with standard tyres	mm	2550	2550	2550	2550	2550	2550
Overall height with standard tyres	mm	3870	3870	3870	3870	3680	3680
Overall height with top frame lowered	mm	3040	3040	3040	3040	3050	3050
Track width	mm	1950	1950	1950	1950	1850	1850
Loading floor height with standard tyres	mm	1340	1340	1340	1340	1180	1180
Permissible gross weight	t	16	16	16	16	13	11
Permissible towbar load	t	2	2	2	2	2	1.2
Axles/tyres							
Steered trailing axle		○	○	○	○	○	–
710/35 R 22.5		●	●	●	●	●	–
620/40 R 22.5		○	○	○	○	○	–
560/45 R 22.5		○	○	○	○	○	–
500/55-20		●	●	●	●	●	–
555/45-17		–	–	–	–	○	○
500/50 R 17		–	–	–	–	○	●
Operation							
Hydraulic spool valves		Load sensing	Load sensing	Load sensing	Load sensing	1 x sa + 1 x da (+1 x sa) ²	1 x sa + 1 x da
ISOBUS control via COMMUNICATOR II		●	●	●	●	–	–
CLAAS CONTROL TERMINAL		–	–	–	–	●	●
Equipment							
Third metering roller		–	○	–	○	–	–
Double wide-angle PTO shaft		○	●	○	●	○	○
Hydraulically sprung drawbar		○	○	○	○	–	–
Lighting kit		○	○	○	○	–	–

● Standard ○ Optional – Not available

¹ Not available in all countries

² For steered trailing axle option

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed in order to present the function clearly in photographs. To avoid any risk of danger, never remove these protective panels yourself. In this respect, please refer to the relevant instructions in the operator's manual.